

PSM-40/230

77707654



Scan this QR code and see the full range



[Link to the product page](#)

Replacement surge cartridge for PSM, Type 2 / Class II, 1 pole, (L-N), 40 kA (8/20), 230 / 400 V, 1 module.

Technical Data	Value	Units
Commercial data		
Code	77707654	
Part Number	PSM-40/230	
Status	Available	
EAN	8435297831761	
Tariff code (HS)	8536.30.90	
Packaging height	80	[mm]
Packaging width	23	[mm]
Packaging length	105	[mm]
Packaging weight	70	[gr]
Packaging unit	1	
Technical features		
No. poles	1	
No. DIN rail modules	1	
Installation	(L-N)	
Format	Pluggable	
Product standards	IEC 61643-1; EN 61643-11	
Certifications	CE	
Designation according to EN 61643-11	Type 2	
Designation according to IEC 61643-1	Class II	
Supply voltage	230 / 400 [V]	

Nominal voltage AC 50-60 Hz (L-N)	Un (L-N)	230	[V]
Maximum continuous operating voltage (L-N)	Uc (L-N)	275	[V]
Maximum discharge current (8/20) (L-N)	Imax (L-N)	40	[kA]
Nominal discharge current (8/20) (L-N)	In (L-N)	20	[kA]
Voltage protection level (L-N) at In	Up (L-N)	1,3	[kV]
Maximum back-up fuse		125	A [gL]
Short circuit withstand	Icc	25	[kA]
Remote indication		No	
Visual end of life indication		Yes	
Dynamic thermal disconnection (L-N)		Yes	
Cartridge color		Grey RAL 7035	
Enclosure		IP 20	
Temperature range		-40 °C ... +80 °C	
Product weight		58	[gr]

More information

More about the product range on page...	43
... of this catalogue	CPT-Cirprotec-V-OVERVOLTAGE-AND-SURGE-PROTECTION [4.05 MB]

Specification data

Unspecified

Wiring diagrams

Unspecified

Address

**Barcelona****Cirprotec, S.L.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

www.cirprotec.com